

CPP Glitter Film with Metallic Gold Flakes Sparkling Shimmer Effect for Decorations & Packaging, Eye-Catching Design

Basic Information

Place of Origin: Zhejiang, China

Brand Name: ZhanxinModel Number: CPP01

Minimum Order Quantity: 30000 square meters

• Price: \$0.16/square meters 30000 square

meters \$0.15/square meters 50000 square

meters

Packaging Details: Wrapping film, Bubble film, Pallet

• Supply Ability: 10000 Square Meter/Square Meters per

Week Most popular all that glitter band film



Product Specification

Industrial Use: Gift & Craft

• Use: Craft, Other Gift & Craft

Material: CPP

Type: Metallized Film
Usage: Decorative Film
Feature: Moisture Proof

Hardness: Soft

Processing Type: Blow MoldingTransparency: Opaque

Product Name: Most Popular All That Glitter Band Film
 Packing: Bubble Film, EPE Film, Carton And Pallet

Substrate: Specialized PP Film

Finish: Metalized, Transparent And Color

Length: 1000 M, 1500 M Per Roll
 Width: 300 Mm - 1500 Mm



More Images







CPP Glitter Film with Metallic Gold Flakes Sparkling Shimmer Effect for Decorations & Packaging

Product Specifications

Attribute	Value
Industrial Use	Gift & Craft
Material	CPP
Туре	Metallized Film
Usage	Decorative Film
Feature	Moisture Proof
Hardness	Soft
Processing Type	Blow Molding
Transparency	Opaque
Packing	Bubble film, EPE film, Carton and pallet
Substrate	Specialized PP film
Finish	Metalized, transparent and color
Length	1000 m, 1500 m per roll
Width	300 mm - 1500 mm
Port	NINGBO, SHANGHAI

Product Description



Thermal Glitter Transparent Lamination Film Roll

The thermal glitter transparent lamination film is used to laminate paper board after printing.

Materials: CPP Basic

Thickness: 110 micron, 120 micron
Width: 1020 mm, 1200 mm, 1300 mm

Length: 1000 m per roll Available Roll Sizes: 300 mm * 100 m 300 mm * 200 m 330 mm * 100 m

330 mm * 200 m

300 mm * 1000 m

500 mm * 1000 m

1020 mm * 1000 m

Customization: Accept customized roll sizes

Packing: Carton, pallet

Delivery time: 3 - 15 days

Key Features

Environmentally friendly: Non-hazardous to health with no toxic gases or volatile content emitted. Safe for laminating process as no solvent-based adhesive is used.

Easy handling: Simple to operate once required temperature is met with no special technique required.

Machine adaptable: Recommended for dry laminators. Can be used in wet laminators with small adjustments.

Process Parameters

Equipment: Dry and wet film laminator

Temperature: Normal: 85~100°C / Special: 100~110°C

Roller pressure: 10~18Mpa

Speed: 8~50m/min

Note: Special laminations refer to those with thicker ink, solid color, high moisture content and bigger size paper.

Application Manual

Adjust roller pressure and temperature according to different types of paper and ink.

When using the film for the first time or changing to other sizes, we recommend a small trial volume before full mass lamination.

Our Services

Free samples available

Response to all inquiries within 7 hours

On-time delivery guaranteed







Frequently Asked Questions

What is your MOQ?

Normally our MOQ for each size is 1 ton, but for first orders we can discuss according to your specific requirements.

Can you offer free sample?

Yes, we offer Size A4 or width 300 mm * length 30 m / roll samples.

What is your delivery time?

We deliver within 10-20 days.

What is your Payment terms?

T/T, L/C at sight.

Can you accept mixed products in one container?

Yes, we accept mixed products in one container.



Wenzhou Zhanxin New Materials Technology Co., Ltd.







holographic-film.com

No.1, Mocheng Industrial Zone, Aojiang Town, Pingyang County, Wenzhou City, Zhejiang, China